

DO'S AND DON'TS OF ALUMINIUM SCAFFOLD



- Do take time to move the scaffold properly and carefully as it may be dangerous if not used properly.
 - Do anchoring at every 4mtrs height beyond 8mtr outdoor & 12mtr indoor areas.
- Do take extra precautions while working with electricity or electrical circuit.

Do install Toe boards so as to prevent falling of hand tools or other working equipment to the lower-level working areas or the ground.

- Do understand the load bearing capacity of the scaffold.
- Do get proper training for proper usage of the scaffold including erection and dismantle.
- Do use 3 point climbing means you need two feet and one hand or two hands and one foot on the scaffold at all times.
- Do always use guardrails, fall arrest systems and safety PPE while working over 10 feet height
- / Do always use Water level to straighten the tower while erection.

/ Do always use proper and complete erected scaffolds.

- / Do always climb the tower from inside.
- / Do ensure that the person using the scaffold should be medically fit.





- Don't move a scaffold with person standing on it. Don't erect or use the scaffold in case of winds exceeding 17mph or during high wind/storm time. (Dismantle the tower during high wind/storm or winds exceeding 17mph.) Don't enter in the range of 4 metres when dealing with electricity or electric lines. Don't use scaffold without Toe boards or Netting. Don't overload the scaffold beyond safe prescribed limits. Don't compromise the safety of your workforce when they are working on a scaffolding system. Don't ignore user manual, as it provided useful information about how to use the scaffold properly. Don't work on height without proper safety equipment including fall arrest systems and quardrails. >> Don't move scaffold on uneven surface. Don't lift the heavy material from outside of the tower. Don't climb the tower from outside.
 - Don't allow any Vertigo or other medical unfit person to climb the scaffold.

